


General Features

- High corrosion resistant performance: Pb-Ca multi-alloy grid
- High energy density and power density
- Optimized capability of instant high-current discharging
- Excellent charge acceptance ability
- Excellent deep cycle discharge capability
- Strong high and low temperature performance
- Precision sealing technology
- Long life


Dimension: 407(L) × 173(W) × 237(H) × 237(TH) / (±3)
Unit: mm


Terminal Dimensions

Specification

Nominal Voltage	12V
Nominal Capacity	120Ah@20hour-rate to 1.75V per cell @25°C
Design life	10 years
Terminal	M8
Approx. Weight	Approx 31.0kg ± 3% (68.34lbs ± 3%)
Container Material	ABS(UL94-HB, UL94-V0 Optional)
short-circuit current	2180A
Internal resistance(Full charged at 25°C:)	5.5 mΩ
Self discharge	3% of capacity declined per month at 25°C

Operating Temperature

Discharge:	-20 ~50°C(-4~ 122°F)
Charge :	-20 ~50°C(-4~ 122°F)
Storage:	-20 ~50°C(-4~ 122°F)

Charge Method(25 °C)

Charge current:	Max. 30A; Recom. 12A
Float charge: 13.5-13.8V	recom. 13.8V(-18mV/ °C)
Equalize charge: 13.8-14.1V	recom. 14.1V(-24mV/ °C)
Cycle charge: 14.4-15.0V	recom. 14.7V(-30mV/ °C)

Standards

Executive standard: IEC 60896-21/22

Applications

- UPS/EPS
- Power systems
- Telecommunications system
- Emergency lighting, Auto control system
- Solar/wind generating storage cyclic
- Other general purpose


Rated Capacity

20Hour Rate (6.0A to 10.5V)	120Ah
3Hour Rate (29.8A to 10.2V)	89.4Ah
1Hour Rate (68.8A to 9.6V)	68.8Ah


Attain Certificate




Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of temperature on float life



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	193.6	117.9	86.7	68.8	51.3	41.2	31.6	25.5	21.7	18.4	14.2	11.8	6.19
1.65V	185.9	113.1	83.3	66.1	49.8	40.3	30.6	24.7	21.1	18.2	14.1	11.7	6.09
1.70V	174.2	108.1	79.6	63.3	47.9	38.6	29.8	24.1	20.6	17.8	13.8	11.5	6.03
1.75V	162.1	102.3	76.1	61.3	45.9	37.2	28.9	23.5	20.0	17.3	13.6	11.4	6.00
1.80V	152.6	99.5	73.3	58.7	43.7	36.1	28.6	22.8	19.5	16.8	13.4	11.2	5.94
1.85V	126.7	84.2	64.0	51.6	39.5	31.9	25.1	20.7	17.8	15.3	12.6	10.3	5.70

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	340	214.1	157.8	125.9	95.1	75.8	59.7	47.7	40.8	35.4	27.8	23.2	12.2
1.65V	329.9	207.7	152.7	122.4	92.7	74.5	58.8	46.6	39.9	35.1	27.5	23	12
1.70V	313.6	200.5	150.9	119.1	91.3	72.1	56.3	45.5	39	34.3	27.1	22.7	11.9
1.75V	296.1	193.6	144.7	116.6	88.8	70.2	56	44.5	38.1	33.6	26.8	22.4	11.8
1.80V	280	186.9	139.2	111.8	84.2	69	54.4	44	37.3	33	26.4	22.2	11.8
1.85V	233.3	162.6	123.7	99.9	78.2	63.2	48.9	40.5	34.9	30.2	24.9	20.9	11.1