


General Features

- ▶ High corrosion resistant performance: Pb-Ca multi-alloy grid
- ▶ High energy density and power density
- ▶ Optimized capability of instant high-current discharging
- ▶ Excellent charge acceptance ability
- ▶ Excellent deep cycle discharge capability
- ▶ Strong high and low temperature performance
- ▶ Precision sealing technology
- ▶ Long life


Dimension: 522(L)×240(W) ×219(H)×222(TH)/(±3)
Unit: mm


Terminal Dimensions

Specification

Nominal Voltage	12V
Nominal Capacity	200Ah@10hour-rate to 1.80V per cell @25°C
Design life	10 years
Terminal	M8
Approx. Weight	Approx 59.0kg±3% (130±3%lbs)
Container Material	ABS(UL94-HB, UL94-V0 Optional)
short-circuit current	3000A
Internal resistance(Full charged at 25°C:)	4.0 mΩ
Self discharge	3% of capacity declined per month at 25°C

Operating Temperature

Discharge:	-20 ~50°C(-4~ 122°F)
Charge :	-20 ~50°C(-4~ 122°F)
Storage:	-20 ~50°C(-4~ 122°F)

Charge Method(25 °C)

Charge current:	Max. 50A; Recom. 20A
Float charge: 13.5-13.8V	recom. 13.8V(-18mV/ °C)
Equalize charge: 13.8-14.1V	recom. 14.1V(-24mV/ °C)
Cycle charge: 14.4-15.0V	recom. 14.7V(-30mV/ °C)

Standards

 Executive standard: IEC 60896-21/22,
 GB/T 19638.1-2014

Applications

- ▶ UPS/EPS
- ▶ Power systems
- ▶ Telecommunications system
- ▶ Emergency lighting, Auto control system
- ▶ Solar/wind generating storage cyclic
- ▶ Other general purpose


Rated Capacity

10Hour Rate (20.0A to 10.8V)	200.0Ah
3Hour Rate (53.2A to 10.2V)	159.6Ah
1Hour Rate (126.5A to 9.6V)	126.5Ah


Attain Certificate

	RoHS


Discharge characteristic




Charging characteristic



The effect of temperature on capacity



The effect of temperature on float life



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	355.8	214.6	159.5	126.5	94.0	75.0	56.4	45.4	38.7	32.9	25.4	21.1	11.0
1.65V	341.8	206.0	153.1	121.5	91.1	73.3	54.7	44.0	37.7	32.4	25.1	20.8	10.9
1.70V	320.2	196.9	146.4	116.5	87.6	70.2	53.2	43.0	36.7	31.7	24.7	20.5	10.8
1.75V	297.9	186.3	139.9	112.8	83.9	67.8	51.6	41.9	35.8	30.9	24.3	20.3	10.7
1.80V	280.6	181.2	134.9	107.9	80.0	65.6	51.0	40.7	34.8	30.0	23.9	20.0	10.6
1.85V	232.9	153.4	117.7	94.9	72.3	58.1	44.8	36.9	31.7	27.4	22.5	18.4	10.2

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	625.1	389.7	290.3	231.6	173.9	138.0	106.4	85.1	72.7	63.1	49.5	41.5	21.7
1.65V	606.5	378.1	280.9	225.0	169.6	135.6	104.9	83.1	71.1	62.6	49.1	41.0	21.4
1.70V	576.5	365.0	277.6	219.1	167.1	131.2	100.5	81.2	69.5	61.2	48.4	40.5	21.2
1.75V	544.3	352.5	266.2	214.5	162.5	127.7	99.8	79.4	68.0	59.9	47.8	40.0	21.1
1.80V	514.8	340.3	256.1	205.6	154.1	125.7	97.1	78.5	66.5	58.8	47.1	39.5	21.0
1.85V	428.9	296.0	227.6	183.7	143.1	115.0	87.2	72.2	62.2	53.8	44.4	37.3	19.7