



General Features

- ▶ High corrosion resistant performance: Pb-Ca multi-alloy grid
- ▶ High energy density and power density
- ▶ Optimized capability of instant high-current discharging
- ▶ Excellent charge acceptance ability
- ▶ Excellent deep cycle discharge capability
- ▶ Strong high and low temperature performance
- ▶ Precision sealing technology
- ▶ Long life


Dimension: 258(L) × 168(W) × 208(H) × 211(TH)/(±3)
Unit: mm


Terminal Dimensions

Specification

Nominal Voltage	12V
Nominal Capacity	80Ah@10hour-rate to 1.80V per cell @25°C
Design life	10 years
Terminal	M6
Approx. Weight	Approx 24.0kg ± 3% (52.9 ± 3% lbs)
Container Material	ABS(UL94-HB, UL94-V0 Optional)
short-circuit current	1818A
Internal resistance(Full charged at 25°C:)	6.6 mΩ
Self discharge	3% of capacity declined per month at 25°C

Operating Temperature

Discharge:	-20 ~50°C(-4~ 122°F)
Charge :	-20 ~50°C(-4~ 122°F)
Storage:	-20 ~50°C(-4~ 122°F)

Charge Method (2 5° C)

Charge current:	Max. 20.0A; Recom. 8.0A
Float charge: 13.5-13.8V	recom. 13.8V(-18mV/ °C)
Equalize charge: 13.8-14.1V	recom. 14.1V(-24mV/ °C)
Cycle charge: 14.4-15.0V	recom. 14.7V(-30mV/ °C)

Standards

 Executive standard: IEC 60896-21/22,
 GB/T 19638.1-2014





Applications

- ▶ UPS/EPS
- ▶ Power systems
- ▶ Telecommunications system
- ▶ Emergency lighting, Auto control system
- ▶ Solar/wind generating storage cyclic
- ▶ Other general purpose

Rated Capacity

10Hour Rate (8.00A to 10.8V)	80.0Ah
3Hour Rate (21.3A to 10.2V)	63.9Ah
1Hour Rate (50.6A to 9.6V)	50.6Ah

Attain Certificate


Discharge characteristic

Charging characteristic

The effect of temperature on capacity

The effect of temperature on float life

Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	147.6	87.6	64.1	50.6	37.6	30.0	22.6	18.2	15.5	13.1	10.1	8.44	4.41
1.65V	141.8	84.1	61.6	48.6	36.5	29.3	21.9	17.6	15.1	13.0	10.0	8.34	4.34
1.70V	132.8	80.4	58.8	46.6	35.0	28.1	21.3	17.2	14.7	12.7	9.87	8.21	4.30
1.75V	123.6	76.1	56.2	45.1	33.6	27.1	20.6	16.8	14.3	12.4	9.74	8.10	4.28
1.80V	116.4	74.0	54.2	43.2	32.0	26.3	20.4	16.3	13.9	12.0	9.57	8.00	4.24
1.85V	96.6	62.6	47.3	38.0	28.9	23.2	17.9	14.8	12.7	10.9	8.99	7.38	4.07

Constant Power Discharge Characteristics Unit: W/cell (25°C, 77°F)

FV/Time	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	259.3	159.1	116.7	92.7	69.6	55.2	42.6	34.0	29.1	25.2	19.8	16.6	8.69
1.65V	251.6	154.4	113.0	90.0	67.8	54.3	41.9	33.2	28.4	25.0	19.6	16.4	8.57
1.70V	239.2	149.0	111.6	87.7	66.8	52.5	40.2	32.5	27.8	24.5	19.4	16.2	8.47
1.75V	225.8	143.9	107.0	85.8	65.0	51.1	39.9	31.8	27.2	23.9	19.1	16.0	8.44
1.80V	213.5	138.9	103.0	82.2	61.6	50.3	38.8	31.4	26.6	23.5	18.9	15.8	8.39
1.85V	177.9	120.8	91.5	73.5	57.2	46.0	34.9	28.9	24.9	21.5	17.7	14.9	7.90